


OUTSIDE MICROMETERS

**INSPECTION
CERTIFICATE**
TRACEABLE TO DKD



3203-25A



ratchet stop



3203-50A



3203-1004A



3203-3006A



friction thimble for one hand operation

Metric (ratchet stop type)

- Graduation: metric 0.01mm imperial .0001"
- Carbide measuring faces
- Meet DIN863-1
- Supplied with setting standards (except 0-25mm and 0-1")

Metric micrometer set (ratchet stop type)

Code	Range	Micrometers Included	Packaging
3203-753A*	0-75mm	3203-25A, 3203-50A, 3203-75A	blow mould case
3203-1004A*	0-100mm	3203-25A, 3203-50A, 3203-75A, 3203-100A	blow mould case
3203-1506A	0-150mm	3203-25A, 3203-50A, 3203-75A, 3203-100A, 3203-125A, 3203-150A	blow mould case
3203-3006A	150-300mm	3203-175A, 3203-200A, 3203-225A, 3203-250A, 3203-275A, 3203-300A	aluminum box
3203-3012A	0-300mm	3203-25A, 3203-50A, 3203-75A, 3203-100A, 3203-125A, 3203-150A, 3203-175A, 3203-200A, 3203-225A, 3203-250A, 3203-275A, 3203-300A	aluminum box

Imperial micrometer set (ratchet stop type)

Code	Range	Micrometers included	Packaging
3203-33A*	0-3"	3203-1A, 3203-2A, 3203-3A	blow mould case
3203-44A*	0-4"	3203-1A, 3203-2A, 3203-3A, 3203-4A	blow mould case
3203-66A*	0-6"	3203-1A, 3203-2A, 3203-3A, 3203-4A, 3203-5A, 3203-6A	blow mould case
3203-126A	6-12"	3203-7A, 3203-8A, 3203-9A, 3203-10A, 3203-11A, 3203-12A	aluminum box
3203-1212A	0-12"	3203-1A, 3203-2A, 3203-3A, 3203-4A, 3203-5A, 3203-6A, 3203-7A, 3203-8A, 3203-9A, 3203-10A, 3203-11A, 3203-12A	aluminum box

Imperial (ratchet stop type)

Code	Range	Accuracy	L	a	b
3203-1A*	0-1"	.00016"	1.260"	.354"	1.102"
3203-2A*	1-2"	.00016"	2.244"	.551"	1.496"
3203-3A*	2-3"	.00020"	3.228"	.591"	1.929"
3203-4A*	3-4"	.00020"	4.213"	.591"	2.362"
3203-5A*	4-5"	.00024"	5.236"	.650"	2.874"
3203-6A*	5-6"	.00024"	6.220"	.650"	3.346"
3203-7A	6-7"	.00028"	7.205"	.764"	4.094"
3203-8A	7-8"	.00028"	8.228"	.764"	4.606"
3203-9A	8-9"	.00031"	9.213"	.764"	5.118"
3203-10A	9-10"	.00031"	10.236"	.764"	5.591"
3203-11A	10-11"	.00035"	11.220"	.764"	6.102"
3203-12A	11-12"	.00035"	12.205"	.764"	6.614"

Imperial (friction thimble type)

Code	Range	Accuracy	L	a	b
3203-1FA*	0-1"	.00016"	1.260"	.354"	1.102"
3203-2FA*	1-2"	.00016"	2.244"	.551"	1.496"
3203-3FA*	2-3"	.00020"	2.244"	.591"	1.929"

* Supplied with manufacturer inspection certificate traceable to DKD Germany or NIST USA