

**DATA  
OUTPUT**

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable  
(code **7306-20**, **7302-SPC5A/SPC5B**, **7305-SPC2A**)


## DIGITAL CALIPERS (STANDARD MODEL)



**1108-150**

(mm)

Code	Range	Accuracy	Thumb roller	L	a	b	c	d
<b>1108-150*</b>	0-150mm/0-6"	±0.02mm	with	236	21	16	16	40
<b>1108-200*</b>	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
<b>1108-250*</b>	0-250mm/0-10"	±0.03mm	with	350	25	20.5	16	60
<b>1108-300*</b>	0-300mm/0-12"	±0.03mm	with	400	25	20.5	16	60
<b>1108-150W*</b>	0-150mm/0-6"	±0.02mm	without	236	21	16	16	40
<b>1108-200W*</b>	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
<b>1108-250W*</b>	0-250mm/0-10"	±0.03mm	without	350	25	20.5	16	60
<b>1108-300W*</b>	0-300mm/0-12"	±0.03mm	without	400	25	20.5	16	60



\* Supplied with manufacturer inspection certificate traceable to NIST